

7.5 HP ROTARY SCREW

74 dBA | 29 cfm @ 125 ps | 26 cfm @ 150 psi

PRODUCT BULLETIN

BASIC COMPRESSOR FEATURES

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME Powder coated air receiver
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin-on oil filter
- Spin-on separator
- TEFC drive motor (3 phase only)
- UL control components



AIR DRYER OPTIONS

- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Tank discharge ball valve

AIR DRYER OPTIONS

- Refrigerated Dryer - for Shop Applications
- Modular Air Dryer capable of -40°C Dew Point available - for outdoor Applications



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw V230 Volt	Amp Draw V480 Volt
RS71V80	1	208-230	80 Gallon Vertical	32	24	76	32	N/A
RS73V80	3	208-230-460	80 Gallon Vertical	32	24	76	18	9
RS71H80	1	208-230	80 Gallon Horizontal	60	24	45	32	N/A
RS73H80	3	208-230-460	80 Gallon Horizontal	60	24	45	18	9

Add -E to model number to make Elite model



403.304.8314 • info@envisionmanufacturing.ca
3410 53rd ave, Lacombe, Alberta T4L 0B5

ENVISIONMANUFACTURING.CA