

# 10 HP RECIPROCATING

78 dBA | 37 cfm @ 125 psi | 35 cfm @ 150 psi

75 dBA | 40 cfm @ 125 psi | 38 cfm @ 150 psi

## PRODUCT BULLETIN

### BASIC COMPRESSOR FEATURES

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME Powder coated air receiver
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin-on oil filter
- Spin-on separator
- TEFC drive motor (3 phase only)
- UL control components



### ELITE COMPRESSOR FEATURES

- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Tank discharge ball valve

### AIR DRYER OPTIONS

- Refrigerated Dryer - for Shop Applications
- Modular Air Dryer capable of -40°C Dew Point available - for outdoor Applications



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS101V80	1	208-230	80 Gallon Vertical	32	24	76	44	N/A
RS103V80	3	208-230-460	80 Gallon Vertical	32	24	76	28	14
RS101H80	1	208-230	80 Gallon Horizontal	60	24	45	44	N/A
RS103H80	3	208-230-460	80 Gallon Horizontal	60	24	45	28	14

Add -E after model number to make Elite Model