

# 5 HP DUPLEX

36 cfm @ 175 psi (Both Compressors Running) | 18.5 cfm @ 175 psi (One Compressor Running)

## PRODUCT BULLETIN

### BASIC COMPRESSOR FEATURES

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-groove B width motor pulley
- 2-piece tank top plate design

### ELITE COMPRESSOR FEATURES

- All basic features
- Automatic tank drain
- Low oil monitor
- Tank discharge ball valve
- Vibration pads

### AIR DRYER OPTIONS

- Refrigerated Dryer - for Shop Applications
- Modular Air Dryer capable of -40°C Dew Point available - for outdoor Applications



Model Number	Phase	Voltage	Tank	Length	Width	Height
DB51H124	1	208-230	120 Gallon	86	30	50
DB53H124	3	208-230-460	120 Gallon	86	30	50