


# 7.5 HP RECIPROCATING

24 cfm @ 175 psi

## PRODUCT BULLETIN

### BASIC COMPRESSOR FEATURES

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design



### ELITE COMPRESSOR FEATURES

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads

### AIR DRYER OPTIONS

- Refrigerated Dryer - for Shop Applications
- Modular Air Dryer capable of -40°C Dew Point available - for outdoor Applications



*Air cooled after cooler on Elite unit*

Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
<b>B71V84</b>	1	208-230	80 Gallon Vertical	32	26	78	32	N/A
<b>B73V84</b>	3	208-230-460	80 Gallon Vertical	32	26	78	18	9
<b>B71H84</b>	1	208-230	80 Gallon Horizontal	63	24	45	32	N/A
<b>B73H84</b>	3	208-230-460	80 Gallon Horizontal	63	24	45	18	9
<b>B71V124</b>	1	208-230	120 Gallon Vertical	42	34	84	32	N/A
<b>B73V124</b>	3	208-230-460	120 Gallon Vertical	42	34	84	18	9
<b>B71H124</b>	1	208-230	120 Gallon Horizontal	70	26	45	32	N/A
<b>B73H124</b>	3	208-230-460	120 Gallon Horizontal	70	26	45	18	9

Add -E after model number to make Elite Model